

NON-SELF PRIMING REGENERATIVE MONOBLOCK PUMP

MAXN SERIES



Features

- High quality aluminum extruded motor body
- TEFC motor (2 pole) suitable for 220 V (+6%, -15%),
- 50 Hz single phase AC power supply
- In-built thermal overload protector (T.O.P.)
- Motor with F class Insulation
- CED coated cast iron hydraulic parts for corrosion free performance

Product Applications:

- Water transfer in domestic applications.
- Gradening, Farm house
- Lifting water to overhead tanks.

Material of Construction

- Pump Casing : CI FG200
- Impeller : Brass
- Adaptor : CI FG200
- Mechanical seal : Carbon vs Ceramic

Model	Power		Pipe Size (Suc x Del)	Total Head in metre													
				6 m	9 m	12 m	15 m	18 m	21 m	24 m	27 m	30 m	33 m	36 m	39 m	42 m	45 m
	kW	HP	mm	Discharge in Litre per Hour													
MAXN2	0.37 kW	0.5 HP	25 mm x 25 mm	1900	1600	1310	1105	840	600	400							
MAXN1	0.75 kW	1.0 HP	25 mm x 25 mm	2700	2400	2200	2050	1850	1720	1570	1390	1250	1080	960	720	550	450

CENTRIFUGAL MONOBLOCK PUMP



Features

- High quality aluminum extruded motor body
- TEFC motor (2 pole) suitable for 220 V (+6%, -15%),
- 50 Hz single phase AC power supply
- In-built thermal overload protector (T.O.P.)
- Motor with F class Insulation
- CED coated cast iron hydraulic parts for corrosion free performance

Product Applications:

- Water transfer in domestic applications.
- Gradening, Farm house
- Lifting water to overhead tanks.

Material of Construction

- Pump Casing : CI FG200
- Impeller : Brass
- Adaptor : CI FG200
- Mechanical seal : Carbon vs Ceramic

Model	Power		Pipe Size (Suc x Del)	Total Head in metre						
				11 m	13 m	15 m	17 m	19 m	21 m	23 m
	kW	HP	mm	Discharge in Litre per minutes						
CMM10EX	0.75 kW	1.0 HP	25 mm x 25 mm	85	78	69	60	49	35	20